VENDED LAUNDRY T-750 EXPRESS STACK WASHER-DRYER





T-750 EXPRESS STACK WASHER-DRYER

Dexter C-Series Powered by DexterLive Controls

Vended laundry solutions you can depend on.

Dexter C-Series vended T-750 stack washer-dryers are engineered to show up for work in even the harshest laundry environments. Featuring DexterLive controls, next generation components, and high quality materials, these space saving combination units are designed to help make you more successful.

A store full of laundry equipment is a big investment and choosing the right equipment is an important decision. Our products will provide you the efficiency, flexibility, performance, and durability you need to be confident in your choice. With lifetime technical support and an industry leading warranty, you can be confident that we will stand behind every stack washer-dryer you invest in.

Contact your Dexter Authorized Distributor today for more details.

DURABLE:

With heavy-duty bearings in cast iron bearing housings, welded steel spiders and shafts, and rugged frame and cabinet designs, Dexter stack washer-dryers are built to last.

The washer design has been tested thoroughly with our 1,000 hour test.

The polished chrome doors and AISI 304 stainless steel tub, cylinder, and panels keep machines looking great for years.

The screw resistant tumbler hole pattern minimizes tumbler damage.

RELIABLE:

We offer an industry leading 10 year limited warranty on the washer unit and a 5 year limited warranty on the dryer.

A 3 year parts warranty covers the rest.

We stand behind every machine you invest in with lifetime technical support.

EFFICIENT:

With a dry-to-dry time of less than one hour, the Dexter stack washer-dryer works fast and efficiently.

Powerful Express 200 g-force extraction removes more water to reduce dry time and helps save on energy costs.

The electronic pressure switch offers a range of water level options to increase efficiency and help save water.

This dryer features a reversing tumbler to help prevent roping with large linens.

INSTALLATION:

This combination unit provides a full laundry solution in a single footprint and is ideal for laundries with limited space.

The adjustable final extract speed allows the unit to fit almost any location.

As shipped, this Dexter product fits through a standard 36" door way.

EMPLOYEE OWNED | MADE IN THE USA | SINCE 1894

DEXTER.COM

2211 WEST GRIMES AVENUE, FAIRFIELD, IOWA 52556 USA

1.800.524.2954

PROFITABLE:

Every Dexter machine is now easier to use with a common user interface on all products, multiple language options, and detailed customer prompts.

DexterLive controls work with DexterLive.com to allow you to create custom programs that fit your business.

A variety of PLUS cycle features and promotion options will help you maximize revenue generation.

OPTIONS:

Available with blue or black graphics, stainless steel or galvanized dryer tumblers, and chrome or stainless steel dryer doors.

Your machines can be shipped with coin acceptors or payment system ready.

Gas models, with propane kits available.

T-750 EXPRESS STACK WASHER / DRYER SPECIFICATIONS

VENDED LAUNDRY

OVERALL SPECIFICATIONS:

Capacity: Dry Weight Capacity (per machine) Washer Cylinder Volume Dryer Cylinder Volume	50 lb 6.5 cu ft 15.8 cu ft	(22.7 kg) (184.1 L) (447.4 L)
Speed: Washer High Extract Speed Washer Intermediate Extract Speed Washer Washing Speed Washer Motor Size Dryer Tumbler Speed Dryer Motor Size	200 g 60 g 0.9 g 3 hp 45 RPM 2 hp & 1/2 hp	(685 RPM) (375 RPM) (43 RPM) (2.2 kW) (1.5 & 0.38 kW)
Airflow (Dryer Only): 60 Hz Model 50 Hz Model	650 cfm 510 cfm	(18.4 M3/min) (14.4 M3/min)
Dimensions: Overall Height Overall Width Overall Depth	87 3/16" 34 1/2" 56 5/8"	(221.5 cm) (87.6 cm) (138.7 cm)
Washer Cylinder Diameter Washer Cylinder Depth Washer Door Opening Floor to Washer Door Bottom	30" 16" 19 1/4" 16"	(76.2 cm) (40.6 cm) (48.9 cm) (40.6 cm)
Dryer Cylinder Diameter Dryer Cylinder Depth Dryer Door Opening Floor to Dryer Door Bottom Dryer Lint Screen Area	32 1/2" 33" 25 5/8" 55 1/8" 544 sq in	(82.5 cm) (83.8 cm) (65.1 cm) (140 cm) (3510 sq cm)
Weight: Net Weight	1600 lbs	(725.7 kg)
Shipping Information: Shipping Weight Shipping Height Shipping Width Shipping Depth	1650 lbs 91 5/8" 35 7/8" 63 1/2"	(748.4 kg) (232.7 cm) (91.1 cm) (161.3 cm)
Installation Recommendations: Minimum Clearance Between Machines Minimum Clearance Behind Machines Minimum Concrete Thickness Make-Up Air Required Exhaust Size	1/2" 24" 8" 1 sq ft 8"	(1.3 cm) (61 cm) (20.3 cm) (929 sq cm) (20.3 cm)

WASHER REQUIREMENTS:

Water I Flow R Pressu Approx Approx Drain D	Requirements: nlet Size ate (per min) re (min/max) imate Water Usage (per cycle) ximate Hot Water Usage (per cycle) Diameter (O.D.) D Center of Drain	3/4" 9 gal 30-120 psi 53.5 gal 10.5 gal 3" 6 5/8"	(19 mm) (34.1 L) (207-827 kPa) (202.5 L) (39.7 L) (7.6 cm) (16.8 cm)		
Electrical Requirements:					
Model -12	Volts / Hz / Phase / Wiring 208-240 / 60 / 1 / 2 wire + ground	Circuit Breaker / Running Amps / Wire Size 20 amp / 8.4 amp / #12			

DRYER REQUIREMENTS:

-12

-39

Gas Requirements (Gas Models Only):

208-240 / 60 / 3 / 3 wire + ground

230 / 50 / 1 / 2 wire + ground

Model	Volts / Hz / Phase / Wiring	Circuit Breaker / Running Amps / Wire Si	
Electr Gas Mo	ical Requirements: odels:		
Gas U 60Hz I 50Hz I		108,000 BTU/hr 96,000 BTU/hr	(31.7 kW) (28.3 kW)
Gas Si Natura	upply Connection al Gas Supply (Water Column) s Supply (Water Column)	1/2" 5-10" 11 1/2 - 14"	(12.7 mm) (12.7 - 25.4 cm) (29.2 - 35.5 cm)

208-240 / 60 / 1 / 2 wire + ground -11 230 / 50 / 1 / 2 wire + ground -39



Circuit Breaker / Running Amps / Wire Size 15 amp / 8 amp / #12 15 amp / 8 amp / 3.5 mm²

20 amp / 8.4 amp / #12

20 amp / 8.4 amp / 3.5 mm²

AGENCY APPROVALS*



54 5/8 3 3/8 - 4 3/4 34 1/2 43 . 87 3/16 78 3/16 0 10 5/8 **1**0 86 9/16 55 1/8 47 1/4 44 3/8 43 6 5/8 16 ŧ. Ľ€ 2 3/4 --١ **---** 27 3/4 ----7 1/4 - 28 7/16 --44 1/2 —

SIDE

Due to continuous product improvements specifications are subject to change, please consult the installation manual for the most accurate information. *Agency approvals may vary depending on the machine configuration, consult Dexter Laundry or your Dexter Authorized Distributor for details.

FRONT

BACK